

CDXconventional

BANSHEE EXCEL LITE IP66

Xenon Conventional Weatherproof Sounder Strobe

Features

- ▶ Robust design
- ▶ Low current consumption
- ▶ Easy to install
- ▶ Xenon beacon technology
- ▶ Maximum 110dB(A) at 1m (dependant on tone selected)
- ▶ 32 user-selectable tones
- ▶ Weatherproof – IP66



Description

The BANSHEE EXCELLITE IP66 combines the modern aesthetics of the multiline sounder and the very latest strobe technology to create an extremely efficient strobe/sounder combination for external applications. It is easily installed with robust terminations that can accept 2.5mm² cables and a push and twist

bayonet-fitting weatherproof base.

Available in a wide choice of lens colours*, the BANSHEE EXCEL LITE IP66 will suit the majority of fire and security needs where a weatherproof conventional sound requires the backup of a visual alarm.

Specification

Ordering codes	BANSHEE EXCELL LITE IP66	
Operating voltage	9 - 30 VDC	
Maximum sound output (@ 24 VDC) (dependant on tone selected)	110 dB(A) @ 1 metre	
Operating current (dependant on tone selected)	min	6 mA
	max	39 mA
Strobe	Current consumption	40 mA (@ 24 VDC)
	Nominal flash energy	1 W
	Flash rate	60/minute
	Lens colour available	Red / Clear* / Green* / Blue* / Amber*
Operating temperature range	- 20 °C to + 55 °C	
Maximum humidity	75% RH - Non-condensing (at 40°C)	
Ingress protection rating	IP66	

*Available upon request – please call for details